

PRODUCT INFORMATION SHEET

Double angled suction cup 50 kg



Product description

The tool is designed for handling and installing, at a selected angle, elements with flat smooth surfaces, such as ceramic tiles, laminated panels, window panes, sheet metal. The mid-length split handle allows for setting the suction cups at an angle (in the range of 90-270 degrees). The handle connection is equipped with a scale for setting the angle and a locking screw. The suction cup body is made of strong and durable aluminium. Thanks to this, the tool, despite its use in demanding conditions, will serve for many years. Moreover, its low weight and the ergonomic shape of the handle improve work comfort. The suction cup is made of durable rubber, which is both flexible and adhesive. Suction by means of a lever. It has a wide range of applications in industries such as tiling, glazing and manufacturing.

Characteristics

- Maximum vertical load capacity 50 kg.
- Working angle 90-270 degrees.
- Number of suction cups on the tool 2.
- Diameter of each suction cup 118 mm.
- Material: aluminium + rubber.

Technical data

| HOSERT | | | |
|---------|---------------|---|----|
| HT3B345 | 5902801468544 | 1 | 20 |

Högert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для: PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków,

Polska/ Poland/ Polen/ Польша

Importer/ Импортер:

- HR GTV Croatia d o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska Distributor:
- ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain
- CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová